



MTENNA^{U7} ASM

(ANTENNA SUBSYSTEM MODULE)

REVOLUTIONARY, GLOBAL, MOBILE CONNECTIVITY

Kymeta's innovative use of metamaterials has solved some of the satellite industry's longest standing technical challenges: the need for lightweight, slim, on-the-move communication systems and services that are easy to buy and understand.

Expand your markets with Kymeta[™] mTenna^{U7} antenna subsystem modules (ASMs). Kymeta mTenna[™] technology provides integration and installation options and flexibility for a variety of applications. There are infinite applications for land, sea, and air – from connected vehicles and trains to ships and construction vehicles, the possibilities are endless.

Flat panel for invisible, seamless,
low-profile installation options

No moving parts for low
maintenance and reliable
connectivity

Access to Kymeta
Partner Portal

Remote updates,
delivering enhanced
performance
improvements and new
features


Tx/Rx on a single
panel

KYMETA[™]

MTENNA^{U7} ASM SPECIFICATIONS

PARAMETER	SPECIFICATION*
Rx frequency range	11.4 - 12.4 GHz
Rx gain	33.0 dB
Rx G/T	9.5 dB/K
Rx scan roll-off @ 60° (H-pol)	1.2
Rx scan roll-off @ 60° (V-pol)	1.1
Rx instantaneous bandwidth	>100 MHz
Tx frequency range	14.0 - 14.5 GHz
Tx gain	32.5 dB
Tx instantaneous bandwidth	>100 MHz
Tx scan roll-off @ 60° (H-pol)	1.4
Tx scan roll-off @ 60° (V-pol)	1.2
Tracking rate	>20°/second
Mobile tracking accuracy	FCC compliant for 25.222 and 25.226
Supported BUC	Pre-engineered for 8 W and 16 W BUC
Temperature range	–25°C to +55°C (operational) –40°C to +75°C (storage)
ASM dimensions	L 82.3 cm x W 82.3 cm x D 7.1 cm L 32.4 in. x W 32.4 in. x D 2.8 in.
mTenna I/O dimensions	W 42.42 cm x D 20.57 cm x H 4.37 cm W 16.7 in. x D 8.1 in. x H 1.72 in.
ASM weight	15.88 kg / 35 lb.
Input power (ASM only) (ASM + mTenna I/O)	100/240 VAC 50/60 Hz 175 W, 15 W typical (system values dependent on BUC) 225 W peak, 20 W typical
Ingress protection	Outdoor unit (ODU): IP66 to protect against weather and environmental conditions expected during operation and storage Indoor unit (IDU**): Rated for use indoors
ASM mounting interface	5/16" x 18 threaded holes, 95 cm (.375 in.) deep on 34.1 cm (13.435 in.) centers. Custom mounting configurations available upon request.

*Specifications are subject to change. **IDU consists of the mTenna I/O, modem, and customer-supplied equipment.



MTENNA^{U7} ANTENNA STACK

- A. Backshell (enclosure)
- B. Control Electronics
- C. Feed Assembly
- D. TFT Aperture
- E. Radome Assembly
- F. Bezel

12277 134th Ct NE, Redmond, WA 98052, USA | +1 (425) 896-3700 | www.kymetacorp.com

twitter.com/KymetaCorp | facebook.com/kymetacorp | instagram.com/kymeta | linkedin.com/company/kymeta-corporation

©2018 Kymeta Corporation. KYMETA, MTENNA, KYWAY, KALO image, and KALO are trademarks of Kymeta Corporation, with registrations or application for these marks pending in Brazil, the European Union, Japan, Norway, Singapore, South Korea, and the United States.