Thuraya W Connecting Everyone Everywhere



Satellite & LTE Hotspot

Staying connected is a priority. It's at the heart of your social identity and self-expression. It's how you reach out to your family and closest friends, to share with them your experiences and news.

We at Thuraya understand this fundamental need, and that's why we have been evolving and advancing our data products throughout the years to meet this ever-growing global demand for wireless data connectivity. Thuraya WE was developed to converge satellite with terrestrial communications. It is the world's first dual mode Satellite & LTE hotspot that keeps you in contact with your family and friends all the time, no matter where you are.

Thuraya We allows you to automatically switch between Satellite and GSM networks with a click of a button using the Thuraya WE mobile app and web interface. With Thuraya WE, you can transform any area into a Wi-Fi hotspot, and allow up to 10 smart devices to connect and share internet within a range of 30m or more.

Product Features

Single SIM, dual mode hotspot

Thuraya WE is the only hotspot in the market to offer dual mode capability. It extends data coverage by offering Satellite & LTE broadband data services allowing you to move in and out of terrestrial coverage areas with ease. You can opt for a Thuraya SIM card and connect to the satellite network or a GSM SIM to enjoy LTE speed. When outside of GSM coverage roam into Thuraya's network using any of our global data roaming partners and stay connected.

Manual or auto-network selection

Thuraya WE enables you to flexibly switch between networks by setting up the auto-network switching function on the web interface or smart phone app. The hotspot will automatically switch from your default network to the other network once you're out of coverage. You can still manually select and switch between networks through Thuraya WE web interface and mobile app by selecting manual network selection.

Calls and text messages in satellite mode



The Thuraya WE app transforms your smart device into a satellite phone, it enables you to access your existing phone's contact list to make satellite calls and SMS's when satellite mode is selected.

 \bowtie

Easy to use interface

To fully control the hotspot, Thuraya has developed a user friendly interface that can be accessed either through the web or through a mobile app compatible with iOS and Android systems. Thuraya WE interface, allows you to easily select and switch between networks, locate the satellite, view signal strength, connection status, battery status, system alerts, data usage reporting, and access device settings.

Unified communications

With Thuraya WE, you can transform any area into a Wi-Fi hotspot, connect all your devices and applications, enjoy the internet by connecting up to 10 smart devices to Thuraya WE within a radius of 30 meters or more.

Lightweight and durable

Weighing 1 kg only, Thuraya WE is compact light and portable, offering voice and data connectivity on the go. It holds the globally recognized Ingress Protection Rating IP54 which provides protection from dust and water spray from any direction to withstand harsh environments.

		CELLULAR SERVICES	CELLULAR SERVICES	
POWER SPECIFICATIONS		Data	3G / LTE	
Rated Input	12V DC, 3A max, 12V + 0.6V	SMS	3G / LTE	
Battery Type	Lithium Ion, rechargeable	Wi-Fi	Wi-Fi	
Battery Capacity	7.4V, 6Ah, (2S2P)	Range	30+ meters Clear line of sight	
Min Charge cycles	300, At 75% Depth of Discharge (DoD)	Number of clients	Up to 10 users	
RUN TIMES (BATTERY)		Security	WPA2 Personal Authentication	
GSM – standby	20hrs	GNSS SUPPORTED SYSTEM	GNSS SUPPORTED SYSTEMS	
GSM – Data	9hrs	GPS, Glonass, Beidou	GPS, Glonass, Beidou	
Sat – standby	6hrs	ROUTER FEATURES	ROUTER FEATURES	
Sat - voice	5hrs	Firewall, Mac Filtering, DMZ, N	Firewall, Mac Filtering, DMZ, NAT, Port Forwarding	
Sat – Data	3 hrs	NATIVE CLIENT APPLICATI	NATIVE CLIENT APPLICATIONS	
PHYSICAL		Android	Minimum version 4.2 (API17), Integrated Phonebook	
Weight	1.00Kg	iOS	Minimum version iOS9, Integrated Phonebook	
Size	230mm x 197mm x 24mm	Published API	For 3rd Party client application development	
DC input Connector	2.5mm ID / 5.5 OD Jack, Centre Positive.	AC CHARGER	AC CHARGER	
SIM Port	Mini	Output	12.0V +5% 36W	
ENVIRONMENTAL		Operating Temperature	0°C to 40°C	
Operating Temperature	-20°C to +55°C, Device ambient temperature	Efficiency Level	VI	
Transport Temperature	-20°C to +60°C, With Battery	TRANSMISSION FREQUEN	TRANSMISSION FREQUENCIES	
Storage Temperature	-20°C to +60°C, With Battery	Satellite	Tx 1626.5-1660.5 Mhz, (earth to space) Rx 1525-1559 Mhz, (space to earth)	
Battery Charging Temperature	0°C to +45°C, Battery Cell Temperature	Satellite		
Humidity	5% to 95% RH, At a temperature of 40 ⁰ C	4G LTE	Band 20 (800 MHz), Band 5 (850 MHz), Band 8 (900 MHz),	
Ingress protection	IP54 compliant	4G LTE	Band 3 (1800 MHz), Band 1 (2100 MHz), Band 7 (2600 MHz)	
SATELLITE SERVICES		3G	Band 5 (850 MHz), Band 2 (1900MHz)	
Voice calls	Circuit Switch	Wi-Fi	Type G, 2.4GHz band IEEE 802.11 b/g/n module	
Data	Up to 384Kbps on standard mode	REGULATORY & APPROVA	REGULATORY & APPROVALS	
SMS	Voice mode only	FCC, CE, Safety IEC 60950 & C	FCC, CE, Safety IEC 60950 & CB certificate, ITU, RCM, REACH, RoHS, IP54	

Product Specifications

Thuraya Customer Care Center From Thuraya network: 100 From other networks: +88216 100 100 Fax: +971 6 8828444 Email: customer.care@thuraya.com

www.thuraya.com

