

Iridium® IoT Product Comparison



	Iridium Edge®	Iridium Edge® Pro	Iridium Edge® Solar
Form Factor	Standalone	Standalone with GPS, Java Programmable	Standalone with GPS, Configurable Profiles
Dimensions (LxWxH)	130 mm x 80 mm x 30 mm	127 mm x 90 mm x 41 mm	164 mm x 71 mm x 33 mm
Weight	330 g	200 g	470 g
Interfaces	AT + Command, RS 232	4 I/O , CANbus, RS 232, RS 485	BLE
Power Requirements	9-32 V	7-40 V	Internal Non-Rechargeable & Solar Chargeable Batteries
Power Consumption (Average)	Transmit Slot (Max) 1.6 W Power On – Max. Current 0.5A Operational – Max. Current 0.3A	Receive : 0.6W GNSS : +0.6W	Harvests Energy from the Sun
Operating Temp. Range	-40°C to + 85°C	-40°C to + 85°C	-40°C to + 85°C
Environmental Specs	SAE J1455**, IP 67	SAE J1455**, IP 67	SAE J1455**, MIL-STD-910, IP 68
Typical Applications	Asset Tracking, Fleet Management, Environment & Safety Monitoring, Remote Automation & Control	Fisheries, Vessel & Fleet Management, Remote Monitoring	Oil & Gas, Transportation, Agriculture, Surface Mining, Asset & Vehicle Tracking
Development Kit	✓	✓	✓
Services	SBD®	SBD®	SBD®
Average Latency	<20 Seconds per 340 Bytes (MO)	<20 Seconds per 340 Bytes (MO)	<20 Seconds per 340 Bytes (MO)
Certifications	US (FCC), EU (CE Mark)**	US (FCC), EU (CE Mark)**	US (FCC), EU (CE Mark)**

Iridium® IoT Product Comparison



	Iridium® 9602	Iridium® 9603	Iridium Core® 9523	Iridium Certus™ 9770
Form Factor	Embedded	Embedded	Embedded	Embedded
Dimensions (LxWxH)	41 x 45 x 13 mm	32 x 30 x 8 mm	70 x 36 x 9 mm	140 x 60 x 16 mm
Weight	30 g	11.4 g	32 g	185 g
Interfaces	AT + Command	AT + Command	AT + Command	“JSON REST over Serial”
Power Requirements	+5 V +/- 0.5 V	+5 V +/- 0.5 V	+3.2 V to +6 V	+12 VDC +/- 2.5 V
Power Consumption (Average)	Idle 35mA Transmit 140mA Receive 40mA	Idle 34mA Transmit 145mA Receive 39mA	Idle 70mA Transmit 300mA Receive 110mA	Idle : 60mW Full Transmit/Receive : 3.5W
Operating Temp. Range	-40°C to +85°C	-40°C to +85°C	-30°C to +70°C	-40°C to +70°C
Environmental Specs	EN60068-2-14:2000 EN60068-2-36:1996 EN60068-2-27:1993 J1455	EN60068-2-27:2009 EN60068-2-14:2009 EN60068-2-64:2008 SAE J1455	EN60068-2-14:2009 EN60068-2-64:2008 EN60068-2-27:2009 SAE J1455 MILSTD 910	EN60068-2-14:2009 EN60068-2-64:2008 EN60068-2-27:2009 SAE J1455
Typical Applications	Personnel & Asset Tracking, Fleet Management, Environment and Safety Monitoring, Remote Automation and Control	Personnel & Asset Tracking, Fleet Management, Environment and Safety Monitoring, Remote Automation and Control	Maritime, Aviation & Mobile Markets	Fleet & Vessel Management, Lone Worker Communications, SCADA, Remote Monitoring
Development Kit	✓	✓	✓	✓
Services	SBD®, Iridium Burst®	SBD®, Iridium Burst®	SBD®, CSD, SMS, RUDICS	Iridium Certus®, IP Data, 2 Voice Lines
Average Latency	<20 Seconds per 340 Bytes (MO)	<20 Seconds per 340 Bytes (MO)	<45 Seconds for 1KB message (MO and MT)*	TBD
Certifications	US (FCC), EU (CE Mark)**	US (FCC), EU (CE Mark)**	US (FCC), EU (CE Mark)**	US (FCC), EU (CE Mark)**

*Latency average assumes data connection established.

**For complete information on local in-country approvals, refer to an authorized Iridium Service Provider.

www.iridium.com

© Copyright 2017-2020 Iridium Satellite LLC. All rights reserved. Iridium, SBD, Iridium Burst, Iridium Edge, Iridium Certus and the Iridium logo are registered trademarks of Iridium Satellite LLC and its affiliates. Information is subject to change without notice.

